





(1) Publication number:

0 305 080 ⁴²

@

EUROPEAN PATENT APPLICATION

(1) Application number: 88307387.6

(a) Int. CI.4. A61B 5/02

@ Date of filing: 10.08.88

Priority: 23.08.87 IL 83615

Oate of publication of application:
 01.03.89 Bulletin 89/09

Designated Contracting States:

AT BE CH DE ES FR GB GR IT LI LU NL SE

Applicant: Frank, Eyal 29 Hamered Street Tel Aviv(IL)

> Applicant: Reich, Yuval Moshav Faren Arava(IL)

Applicant: YISHUVEI POALEI AGUDAT ISRAEL AGUDAH SHITUFIT MERCAZIT LTD 64 Frishman Street Tel Aviv(IL)

inventor: Frank, Eyal
29 Harnered street
Tel Aviv(IL)
Inventor: Reich, Yuval
Moshav Faran
Arava(IL)
Inventor: Noy, Shraga
Kibbutz Hafetz Haim
Doar Hafetz Haim(IL)

Representative: Morton, Colin David et al Keith W Nash & Co. Pearl Assurance House 90-92 Regent Street Cambridge CB2 1DP(GB)

Portable apparatus for continuously monitoring peripheral blood flow.

© Portable apparatus for monitoring peripheral blood flow comprising, according to one embodiment, apparatus for sensing infrared emissions from a bloodstream, including signal generating apparatus for generating a signal of an intensity corresponding to the intensity of an infrared emission sensed by the infrared sensing apparatus. According to an alternative embodiment, the apparatus for monitoring comprises apparatus for directing infrared radiation towards the bloodstream of a user; apparatus for neceiving infrared radiation reflected from the bloodstream of the user; and apparatus associated with the apparatus for directing and the apparatus for receiving for measuring the difference b tween the

infrared radiation transmitted to the bloodstream and the infrared radiation reflected from the bloodstream, including apparatus for generating a signal of an intensity corresponding to the intensity of the difference. The apparatus for monitoring also comprises a power source, electronic control apparatus selectably connectable to the power source including apparatus for receiving a signal from the signal generating apparatus and alarm apparatus associated with the signal receiving apparatus for emitting an alarm output if no signal of at least a salected minimum intensity is received by the signal receiving apparatus from the signal generating apparatus within a selected period of time.




FIG 1